

CONFIDENTIAL

STAT

CONFIDENTIAL

Name of Oil	Number of Standards	Number of Methods Used	Remarks
	Industrial Oils		
1. Vaseline solar	GOST 1665-42 GOST 1666-42	1	
2. Vaseline MVP	GOST 1805-42	1	
3. Spindle	GOST 1837-42	1; 2; 4	Methods No 2 and No 4 are used for reclaiming industrial oil from circulatory systems and after it has been used for lubricating combustion chamber parts of engines; also for reclaiming cylinder "2" after it has been used for lubricating compressors.
4. Machine	GOST 1707-42	1; 2; 4	
5. Cylinder "2"	GOST 1841-42	1; 2; 4	

Oils for Internal Combustion Engines

1. Aviation	GOST 1013-41 TU HarKorMef No 118-42, OST NKPP 446	1; 2; 6	Method No 1 is used at field aerodromes and aircraft plants.
-------------	---	---------	--

Introduced by the Main Administration for Supplying the National Economy with Petroleum Products in SovHarKor, USSR

Confirmed by the All-Union Committee of Standards as recommended 21/VIII 1943

2. Avtols	GOST 1862-42	1; 2; 6; 7	1. Method No 1 is used in field garages; in this, reclaimed oil must be mixed with fresh oil (about 60% fresh and 40% spent oil). 2. Method No 2 is used for reclaiming oils which are collected separately after being used in gas generator motors.
3. Diesel	GOST V 1600-43	1; 2; 6	
4. Migrol	GOST 542-41	1	
5. Motor	GOST 1519-42	2; 6	

Special Lubricating Oils

1. Turbine	GOST 32-42	2; 3; 4; 5; 6	1. Method No 2 is used for spent oil with an oxygen count up to 0.25 mg HON, and methods No 3 and No 4 for oils with an oxygen count up to 0.5 mg HON. 2. Method No 6 is used without distillation of the fuel.
2. Compressor	GOST 1861-48	2; 4; 6	
3. Naval	GOST 2022-43	1	
4. Axle	GOST 610-42	1	

Oils for Steam Engines

1. Viscosine	GOST 1839-42	2; 4	
2. Vapor, vapor petroleum asphalt	GOST 788-43		
3. Cylinder "6"	GOST V-2031-43 OST 10001-38	2; 4 2; 4	

- 2 -

CONFIDENTIAL

CONFIDENTIAL

CONFIDENTIAL
CONFIDENTIAL

STAT

Special Purpose Oils

- | | | | |
|----------------|---------------|-------------|---|
| 1. Transformer | GOST 982-43 | 2; 3; 4; 5; | Method No 2 is used for spent oil with an oxygen count up to 0.25 mg KON, and methods No 3 and No 4 for oil with an oxygen count up to 0.5 mg KON |
| 2. Sulfofrezol | GOST V-122042 | 1 | Oil is subjected to sulfuring. |

NOTE: The methods of reclamation established by this standard do not apply to saponified auto tractor oils and distilled industrial oils.

- END -

- 3 -

CONFIDENTIAL

CONFIDENTIAL